




### Turning the Corner on Crane Operator Safety

Available in new TIDD PC28's

or Retro Fit your TIDD PC25

Slew Safe delivers peace of mind for drivers, dogman, crane owners and site owners, with improved safety, risk management and duty of care.

Slew Safe simply and effectively allows the TIDD PC28 and PC25 operator to pick and carry a load knowing that they will be warned and restricted. No other pick and carry crane is this safe.



**PC25** 

000

TRT's TIDD PC28 is extremely maneuverable, slewing up to 44° working well inside the radius of other pick and carry cranes in its class. At only 2.5m wide the PC28 has a smaller foot print, with Slew Safe it's now even safer!

This is the only pick and carry crane with this level of safety

Australian Innovation Patent No. 2019100317



ww.trt.co.nz

### www.trtaustralia.com.au



(H)

0Y

>

>

>

>

0 4

H

(RPH)

70

11 21.44t

7.87t

704

100

Main hoist manual retracted

7.53t

7.63t

101%

OVERLOADED Steer limit LEFT

# How Slew Safe Works

When the crane in operation moves from green and amber to **RED**, this is an overload notification (based on the lifting chart). This will activate the Slew Safe.

When the crane is operated in the **GREEN** and AMBER areas of the lifting chart, Slew Safe will remain inactive.

> 7.53t 7.63t

101% OVERLOADED Steer limit LEFT

**PC28** 

×

(H)



- Reduce speed of the steering to 15%
- Make the steering harder with feedback through the steering wheel to operator

Duty

101

-20°

6.08m

3.74m

7.13m

26.56

**[** ))))

The engine will "load up" making an audible sound change for operator Audible constant alarm inside and outside cabin to warn operator and dogman of overload.

< |

<

<

<

- Retain ability to move back to safe operation zone **GREEN**

## TIDD PC28 The Safest in its Class

#### Slew Safe is the latest innovation to turn the corner on crane safety!

Other safety features that make TIDD PC28 the safest pick and Carry Crane for your operation include:

- Higher operator position allowing better visibility.
- Superior stability with front hydraulic suspension.
- Dynamic LMI with a deadlock switch inside the cabin and bridging switch outside the cabin.
- ROPS Cabin with FOPS option and 150kg rated air suspension seats with 3-point integrated safety belts.
- ABS brakes.

Contact us for a copy of the new TIDD PC28 charts, manuals or the Slew Safe technical overview.

Distributed by:

Designed & Manufactured by:



#### **Tidd Ross Todd Ltd**

48 Maui Street, Pukete Industrial Estate P.O Box 10076, Te Rapa, Hamilton 3241 Phone: +64 7 849 4839 Email: cranesales@trt.co.nz www.trt.co.nz

TRT (AUST) PTY. Ltd.

1028 Lytton Road, Murarrie, QLD 4172 Phone: +61 7 3890 8800 Email: cranesales@trtaust.com.au www.trtaustralia.com.au